




Elastflex Stadium

A FLOOR THAT FITS ALL

- Low build height



T79 Sports Finish
Squash Finish

The Elastflex construction is extremely strong when supported on by the subfloor. It's good for a low build height requirement.

An area-elastic sports floor made up of an elastic layer and load distribution layer of plywood. Topped with 14mm 3-strip hardwood board.

Can be installed on an even and self supporting subfloor or on top of an existing floor.

Area-elastic sports floor

USAGE: Sports and multipurpose centres.

PERFORMANCE ACCORDING TO EN14904	SHOCK ABSORPTION	DEFORMATION	FRICTION	BALL BOUNCE	ROLLING LOAD MIN. 1500N
Elastflex					
STADIUM	Type 4: 61%	Type 4: 3.5mm	86	96%	OK




Elastflex Stadium





A FLOOR THAT FITS ALL



3-strip



Tongue & groove

Wood species / Grading		Package overview
 Ash Sport	 Beech Sport	Pack Size: 6 boards = 2.76m ² (23kg) Pallet Size: 50 packs = 138m ² (1150kg) We reserve the right to deliver one element as random length in each pack.
 Maple Can. Sport	 Oak Sport	
FSC™ on demand.		

Elastflex Stadium Construction Details (from the top to the edge of concrete/subfloor)		Height
Elastflex Stadium Board • Hardwood Top-Layer 3.5mm • Middle layer and bottom layer spruce The board is nailed into the counter floor.	Elastflex board size : 14 x 209 x 2200mm	14mm
PE Plastic Sheet Laid out loosely, approx. 100mm overlapped at the joints	0.05mm per roll 100m ²	0.05mm
Load distribution Layer According to DIN 68705 part 3. Laid out loosely, intermittently displaced Centre to centre: approx. 137mm	Plywood Birch Stripes, (BFU 100 C/C): 9 x 100 x 2500mm	9mm
Elastic Layer Laid out loosely, intermittently displaced	VB plates RG90: 15 x 1510 x 2240mm = 3.38m ²	15mm
Perimeter boards	15 x 100 x 2500mm	✓
PE Foil (ordered separately)	Special requirement for new buildings: 2 layers of 0.2mm. It is not a moisture barrier, but gives to the floor an extra protection	0.4mm
Construction height		38mm

Maintenance

We recommend starting a regular system of maintenance from day one. The amount of maintenance your floor requires will depend on how you use and treat it. For more information: boensport.com

The environment is at the core of all we do

BOEN hardwood flooring is a product of nature. As a procurer of timber BOEN has an important heritage to maintain. Constant involvement in resource preservation methods, participation in reforestation programmes and the development of alternatives to exotic species shows Boen's dedication towards the environment.

All timber purchased by BOEN is supplied from sources who belong to one or more forestry schemes or are working towards certification.

BOEN Bruk (Norway) FSC™ C051117, BOEN Parkett Deutschland (Germany) FSC™ C101713, BOEN Lietuva (Lithuania) FSC™ C021510, BOEN UK FSC™ C047288, BOEN US FSC™ C095158. www.fsc.org, FSC – The mark of responsible forestry.



-part of the game!

boensport.com